

# DELTA4000 Series 12 kV Insulation Diagnostic System



- Easy to use with automatic and manual operation
- Accurate and repeatable measurement results with high noise suppression for the most extreme conditions
- Lightweight, rugged two-piece design, with unit weights of 31 lb and 48 lb
- New built-in intelligent temperature correction, eliminates the need for temperature correction tables (patent pending)
- New automatic voltage dependence detection (patent pending)
- Performs Doble test (insulation power factor); also imports or exports data from DTA software to PowerDB
- Dedicated engineering support team, available 24/7
- Priority Access support includes extended warranty, annual training, and loaner unit

## DESCRIPTION

The new DELTA4000 Series is a fully automatic 12 kV insulation power factor/dissipation factor ( $\tan\theta$ ) test set designed for condition assessment of electrical insulation in high voltage apparatus such as transformers, bushings, circuit breakers, cables, lightning arresters and rotating machinery. In addition to performing insulation power factor tests, the DELTA4000 Series can be used to measure the excitation current of transformer windings as well as to perform automatic tip-up tests and HV turns-ratio testing (an optional TTR Capacitor is available).

The test set is designed to provide a comprehensive AC insulation diagnostic test. The high power variable frequency design generates its own test signal independent of line frequency quality and the hardware design uses the latest technology available for digital filtering of the response signal. As a result, the DELTA4000 Series produces reliable results and stable readings in the shortest time with the highest accuracy, even in high interference substations.

The DELTA4000 Series operates with PowerDB software for automatic testing and reporting or with Delta Control software for real-time manual testing.

Measurements include voltage, current, watts (loss), power factor and capacitance. The test results are automatically stored in the computer and can also be downloaded directly to USB storage or a printer.

DELTA4110 test set is to be used with an external computer (not included) while the DELTA4310 test set comes with an onboard computer.

## APPLICATIONS

- Power transformers
- Distribution transformers
- Instrument transformers
- Rotating machines
- Oil insulation
- Bushings
- Cables
- Capacitors
- Circuit breakers
- Surge arrestors

## TEST CAPABILITIES

- Power factor
  - Dissipation factor ( $\tan\theta$ )
  - Excitation current
  - Automatic tip-up
  - Watts loss
  - Inductance
  - Capacitance
  - Voltage
  - Current
  - Turns ratio\*
- \* with optional accessory



DELTA4110 test set  
to be used with external  
computer



DELTA4310 test set with  
onboard computer

**FEATURES AND BENEFITS****Industry-Leading Performance and Accuracy**

- **Generates its own test signal** – resulting in accurate and clean measurements even in the most severe conditions and in the event power is required from a portable generator.
- **High noise suppression** and advanced signal acquisition circuitry can handle up to 15 mA interference current or a signal to noise ratio of up to 1:20 resulting in extremely accurate and clean measurements even in the most severe conditions.
- **Industry leading frequency range** (1-500 Hz) reveals details in the insulation characteristics that are not possible to detect with other test sets.
- **Intelligent temperature correction** (patent pending) allows the user to estimate the actual temperature dependence of the test object by measuring power factor over a frequency range. Mathematically calculating accurate individual temperature correction results in a more accurate measurement of the insulating material's condition.
- **Automatic voltage dependence detection** (patent pending) Various high voltage components may have a voltage dependence where tip-up testing is recommended (i.e. the power factor is pending test voltage). The DELTA4000 Series has a patented method for detecting voltage dependence and gives the user an alarm, suggesting additional tests should be performed at different voltage levels.
- **Fast test time** - Dynamic noise suppression minimizes actual test time.
- **Performs Doble testing**. When a Doble test is required or specified, be assured the Megger DELTA4000 Series performs all your Doble testing needs.

**Industry's Lightest and Most Rugged**

- **Industry's lightest** two-piece design, weighing 31lb + 48lb saves on effort, space, and shipping costs.
- **Designed for various work environments:** in the field; in a test van; in a manufacturing facility; or in a repair facility.
- **Units have performed successful testing** in the world's most extreme conditions including: high temperatures, low temperatures, high elevations, high noise, and high humidity.

**Software Package — PowerDB Advanced**

- **Automatic and manual operation** – provides fully automatic operation for power factor as well as excitation current and tip-up testing. The user simply selects the test object and the unit will automatically run the complete test and report the results back to the test form. The DELTA4000 Series can also be used with Delta Control software in a manual testing mode, where the operator has full control to set the test parameters.
- **Easy to save and retrieve data** – information will be saved in an XML file with all historical data. This allows the user to view previous year's test sheet or trend specific test points.
- **Simple, intuitive, easy-to-use interface** between operator and instrument.

- **Suspect data points are flagged** visually with a red highlight.
- **Capability to trend** a specific asset over time.
- **Easily recall transformer setups** from the settings menu.
- **Ability to interface with other transformer test units** such as TTR-series (transformer turns ratio), MTO210 (winding resistance), MIT/S1-series (DC insulation), MCT-series (CT measurements).

**Optional Database Software - PowerDB Pro**

A comprehensive Acceptance and Maintenance Test Data Management Software and database that allows you synchronize information from all of your different types of instruments into a single database, trend test results to similar equipment and the ability to design or modify test forms.

- **Easily import your historical data points** even from other manufacturers' databases.
- **Analysis and trending** - As an immediate on-site assessment the user can compare the latest measurements with stored data and see how the insulation values may have changed over time (trending). Comparison of measurements captured at different voltages and different frequencies can also be observed. Pass/Fail criteria can be set to immediately identify a possible problem in your insulation.

**PRIORITY ACCESS SUPPORT**

Megger now offers a solution enabling you to purchase a complete package of support or individual items based on your needs. Available in 1-yr, 3-yr and 5-yr agreements. Not available in all areas. Please contact your nearest Megger for details and eligibility.

- **Extended product warranty** protects your unit beyond the standard manufacturer's warranty.
- **Training onsite** for the equipment, software, theory, field testing, data analysis, and PowerDB. Training can also be offered at any of the Megger facilities.
- **Loaner units and loaner accessories** provide guaranteed reliability. Loaners delivered within 1-2 business days
- **PowerDB software maintenance and upgrades** as a DELTA4000 customer experience the state-of-the-art communications and data analysis tool with up to the minute upgrades and support
- **Engineering consulting and results analysis** receive guidance through installation, importing older data, customizing forms, comparing results, and data trending.
- **24/7 Technical Support** provided by former utility engineers and PhD's who have vast substation and transformer experience to guide you through your testing procedures and answer your questions.

**SPECIFICATIONS****Input Power**

100-240 V  $\pm$  10 %, 50/60 Hz, 16 A max

**Output Voltage**

0 to 12 kV, continuously adjustable

**Test Frequency Range**

45-70 Hz (12 kV)

15-400 Hz (4 kV)

1-500 Hz (250 V)

**Output Power**

3.6 kVA

**Output Current**

300 mA (4 minutes)

100 mA (continuous)

The power supply capacity can be expanded to 4 A at 12 kV using the optional Resonating Inductor, catalog number 670600.

**Measuring Ranges****Voltage**

25 V to 12 kV, 1 V resolution

**Current**

0 to 5 Amps, 0.1  $\mu$ A maximum resolution. The measurement can be corrected to either 2.5 kV or 10 kV equivalents.

**Capacitance**

0 to 100  $\mu$ F, 0.01 pF maximum resolution

**Inductance**

6 H to 10 MH, 0.1 mH maximum resolution

**Power Factor**

**PF:** 0-100% (0-1), 0.001% maximum resolution

**Dissipation Factor**

**DF:** 0-100 (0-10,000%), 0.001% maximum resolution

**Watt Loss**

0 to 2 kW, actual power, 0 to 100 kW when corrected to 10 kV equivalent. 0.1 mW maximum resolution. The measurement can be corrected to either 2.5 kV or 10 kV equivalents.

**Temperature Correction****Intelligent temperature correction**

from 5° C to 50° C insulation test temperature to 20° C reference

**Standard tables**

as by international standards and manufacturers' data

**Accuracy**

Voltage  $\pm$ (1% of reading + 1 digit)

Current  $\pm$ (1% of reading + 1 digit)

Capacitance  $\pm$ (0.5% of reading + 1 pF)

Inductance  $\pm$ (0.5% of reading + 1 mH)

Power Factor  $\pm$ (0.5% of reading + 0.02%)

Dissipation Factor  $\pm$ (0.5% of reading + 0.02%)

Watt Loss  $\pm$ (1% of reading + 1mW)

**Measurement**

The following test modes are available:

**UST: Ungrounded Specimen Testing**

**UST-R: UST:** Measure Red, Ground Blue

**UST-B: UST:** Measure Blue, Ground Red

**UST-RB: UST:** Measure Red and Blue

**GST: Grounded Specimen Testing**

**GST-GND: GST:** Ground Red and Blue

**GSTg-R: GST:** Guard Red, Ground Blue

**GSTg-B: GST:** Guard Blue, Ground Red

**GSTg-RB GST:** Guard Red and Blue

**Noise Immunity****Electrostatic**

15mA induced noise into any test lead with no loss of measurement accuracy at maximum interference to specimen current of 20:1

**Electromagnetic**

500  $\mu$ T, at 60 Hz in any direction

**Computer Interface**

Ethernet and USB

**PC Requirements****DELTA4110**

**Operating system:** Windows XP/Vista/7

**Processor:** Min Pentium 1 GHz

**Memory:** Min 1024 Mb RAM

**Hard drive:** Min 1 Gb available

**Interface:** USB and Ethernet

**DELTA4310**

Internal PC with 8.4" full-color VGA, full QWERTY keypad, navigational pushbuttons, and joystick (external mouse can be connected) on-screen view of test forms, USB printer interface.

**Communication/Control/Data Management Software**

PowerDB and DELTA Control

**Safety Qualifications**

IEC / ANSI 61010-1

**Environment****Temperature**

**Operating:** -4 to +131° F (-20 to +55° C)

**Storage:** -58 to +158° F (-50 to +70° C)

**Relative Humidity**

**Operating:** 0 to 95% non-condensing

**Storage:** 0 to 95% non-condensing

**Shock and Vibration**

ASTM D999.75

**EMC**

EN 61326

**Dimensions**

**Control Unit:** 11 x 11 x 18 in. (290 x 290 x 460 mm)

**High Voltage Unit:** 11 x 11 x 18 in. (290 x 290 x 460 mm)

\*Does not include handles.

**Weight**

**DELTA4100 Control Unit:** 31 lbs (14 kg)

**DELTA4300 Control Unit:** 33 lbs (15 kg)

**DELTA4010 High Voltage Unit:** 48 lbs (22kg)

**Cables:** 33 lbs (15 kg)

**ORDERING INFORMATION**

Item [Qty]	Cat. No.	Item [Qty]	Cat. No.
DELTA4110 Insulation Diagnostic System (DELTA4100 control unit and DELTA4010 HV unit)	DELTA4110	<b>Optional Accessories</b>	
DELTA4310 Insulation Diagnostic System with onboard computer (DELTA4300 control unit and DELTA4010 HV unit)	DELTA4310	Safety foot switch	1001-852
<b>Included Accessories</b>		External strobe	Y37181
High voltage lead: 70 ft (21 m), double shielded	30012-11	External strobe extension cable, 18 m (60 ft)	1001-853
Measurement lead, color-coded red	25572-1	Transport case, 2-piece design kit, consists of: case for control unit and accessories (2001-746), case for HV unit and accessories (2001-746)	1001-932
Measurement lead, color-coded blue	25572-2	Transport case, 3-piece design kit, consists of: case for control unit (2001-791), case for HV unit (2001-791), case for accessories (2001-792)	1001-933
Ground lead: 30 ft (9 m)	2002-131	Transport cart / trolley	1001-530
Input power cable 16A EU	17032-19	Calibration box set for CAL4000	2002-137
Input power cable 16A US	17032-20	Calibration standard	670500-1
Input power cable 16A UK	17032-21	Transit cases for calibration standard	670635
Input power cable 16A no plug	17032-22	HV TTR capacitor, single phase (10 nF, 10 kV)	36610
Safety hand switch, Interlock #1: 18 m (60 ft)	1001-850	HV reference capacitor (100 pF, 10 kV)	36610-1
Safety hand switch, Interlock #2: 2.5 m (8 ft)	1001-851	HV reference capacitor (1000 pF, 10 kV)	36610-2
HV unit power cable, 1 m (3 ft)	2002-132	Carry case for capacitors	36610-CC
HV unit control cable, 1 m (3 ft)	2002-133	Capacitor kit (TTR cap, 2 ref caps, carry case)	36610-KIT2
Ground lead cable, 1 m (3 ft)	2002-134	Resonating inductor	670600-1
USB cable, 3 m (10 ft)	2002-135	Thermal Pentax® printer, 120 V	36493-1
Ethernet cable, CAT 5, 3 m (10 ft)	2002-136	Thermal Pentax® printer, 240 V	36494-1-KIT
Soft padded carrying case for control unit [1]	2001-766	Thermal paper (8.5" x 11") for printer	36809-1
Soft padded carrying case for HV unit [1]	2001-766	Thermal paper (A4) for printer	36809-2
Soft case for HV cable	2001-507	Oil test cell	670511
Soft case for other cables/accessories	2001-506	Hot collar belts [3]	670505
User manual	81331	Bushing tap connectors [2]	670506
Application guide	81332	External temperature and humidity probes	2002-138
Warranty [1 year]		USB bar code wand and software	36528
PowerDB Advanced software		Accessory kit: hot collar straps [3], external temperature and humidity meters, .75" bushing tap connector [1], 1" bushing tap connector [1], mini bushing tap connectors [2], "J" probe bushing tap connector [1], 1 m (3 ft) non-insulating shorting lead [3], 2 m (6 ft) non-insulating shorting lead [3]	670501
<b>Optional Software</b>		Special length cables available upon request	Consult factory
PowerDB Pro software, on USB dongle	DB1001S-A	<b>Additional Transformer Test Products</b>	
PowerDB Pro software, via soft key	DB1001-A	Leakage Reactance	MLR
<b>Extended Warranty and Annual Support</b>		Turns Ratio, 3-phase	TTR
Priority Access annual support plan	D4K-P-ACCESS	Winding Resistance	MTO
Extended product warranty	Y12-WARRANTY	Sweep Frequency Response Analysis (SFRA)	FRAX
Training	D4K-TRAINING	Dielectric Frequency Response (DFR) and moisture assessment	IDAX
Loaner unit and accessories	D4K-LOANER	DC Insulation	MIT/S1
PowerDB software maintenance and upgrades	D4K-SOFTWARE	Current Transformer Measurements	MCT
Engineering consulting and results analysis	D4K-ENGCONSULT		
24/7 technical support	D4K-TECHSUPPORT		

**UK**  
Archcliffe Road, Dover  
CT17 9EN England  
T +44 (0) 1 304 502101  
F +44 (0) 1 304 207342  
UKsales@megger.com

**UNITED STATES**  
4271 Bronze Way  
Dallas, TX 75237-1019 USA  
T 1 800 723 2861 (USA only)  
T +1 214 333 3201  
F +1 214 331 7399  
USsales@megger.com

**OTHER TECHNICAL SALES OFFICES**  
Valley Forge USA, College Station USA, Sydney AUSTRALIA, Täby SWEDEN, Ontario CANADA, Trappes FRANCE, Oberursel GERMANY, Aargau SWITZERLAND, Kingdom of BAHRAIN, Mumbai INDIA, Johannesburg SOUTH AFRICA, and Chonburi THAILAND

**ISO STATEMENT**  
Registered to ISO 9001:2000 Cert. no. 10006.01  
**DELTA4000\_DS\_NAFTA\_V01**  
www.megger.com  
Megger is a registered trademark  
All information contained herein is subject to change without notice